

„ATIFARB” Sp. z o.o.
ul. Jagiellońska 85/87
42-200 Częstochowa
tel/fax: (034) 36746 06
e-mail: atifarb@o2.pl
www.atifarb.pl



KRS: 0000214018

NIP: 949-08-89-013

IDS: 150305660

ATIGRUNT

Composition primer **PN-C-81906:2003**

TECHNICAL CHART

DESCRIPTION

Ecological priming agent applicated for a purpose of decrease of absorbability and increase adhesion to the foundation penetrating deep.

The priming agent in a liquid state, light – milk colour, prepared on a base of modified synthetic resin. Let pass water vapor, control a process of absorption, transparent when dry. It penetrate intensively the foundation strengthening it and increasing adhesion.

PURPOSE

Its purpose is following : priming most of porous and absorbing internal and external surfaces of building objects. Priming brickwork before plastering gypsum plaster or cementation of gypsum plates.

Clear coat gypsum plasters or gypsum platters before painting, paper – hanging or covering by additional finishing rendering.

PROPERTIES

Coats obtained as the result of a proper application of the ATIGRUNT is characterized by:

high adhesion;
low internal strain;
possibility of spreading by a brush and a roller;
proper permeability of water;
equalization of absorbability of the foundation;
high junctive properties.

Technical properties of paints and coats are shown in table in details :

Granulation	No concern
Density	1g/cm ³
Time of drying	about 3 h, it depend on absorption of foundation

Temperature of application	>5°C (environment and foundation)
Colour	Light-milk
Expenditure	0,12 l/m ²
Storage	in temp. above 0°C don't allowed to get frozen
Package	1l, 5l containers

Guidelines of painting

PREPARATION OF SURFACE

The surface should be clean and dry before using AtiGrunt unfixed and loosed parts should be remove prior to application of the product.

THE WAY OF APPLICATION

AtiGrunt is supplied as the solution ready for using, dilution of the product is not recommended. The method of its application depend on conditions and the foundation. It can be put on by a paintbrush, a painting roller or by spraying with preserving uniformity of spreading. We use product only once on a chosen surface. If the foundation is high absorptive, it is necessary to repeat priming using a solution AtiGrunt in water (ratio 1:1) on still wet primary layer of primer.

EXPENDITURE

Efficiency of the product depend closely on absorption and condition of the foundation. It is 7-10m²/l. respectively.

TIME OF DRYING

Over 3 hours, however, it closely depend on absorption of the foundation and climatic conditions and can be prolonged.

Indications

Use on the dry, clean and not frozen foundation. Use in temp. above +5°C. Wash tools directly after using. Store at a cool place, in temp. above 0°C. Admitted period of storage is 12 months.